

AMENDMENT IN THE SPECIFICATION

Under 37 CFR 1.121 and 1.125 please replace the entire specification with the attached substitute specification. The substitute specification includes no new matter. The following indicates the changes made to the attached substitute specification.

TITLE:

~~FLAT PLATE HEAT EXCHANGER COIL AND METHOD OF OPERATING THE SAME~~
FLAT HEAT EXCHANGER PLATE AND BULK MATERIAL HEAT EXCHANGER USING THE SAME

BACKGROUND OF THE INVENTION

Field of the Invention

[001] The present invention relates generally to ~~coils~~ flat heat exchanger plates for use in heat exchangers. More particularly, relating to ~~flat plate coils~~ flat heat exchanger plates used in bulk material type heat exchangers.

[002] Typically, in processing bulk materials, such as pellets, granules, powders or the like, heat exchangers are employed to either cool or heat the material during the processing thereof. The heat exchangers employed consist of an array of ~~plate-like coils~~ plate heat exchangers arranged side-by-side in spaced relationship and are positioned in an open top and open bottom housing. The like ends of each ~~coil~~ heat exchanger plate are connected to together by means of a manifold and a heat exchange medium, such as water, oil, glycol or the like is caused to flow through the ~~coils~~ plates. Generally, the material treated by the heat exchanger is allowed to gravity flow through the housing and the spaces between the spaced ~~plate-coils~~ plates. During the progression of the material through the heat exchanger, the material is caused to contact the walls of the ~~plate coils~~ plates thereby effecting heat transfer between the material and the ~~plate-coils~~ plates. The rate at which the material flows through the heat exchanger and ultimately across the ~~plate-coils~~ plates can be controlled by restricting the flow of the material at the outlet of the heat exchanger.

[003] The ~~plate-coils~~ heat exchanger plates are constructed by attaching metal sheets together along the edges thereof and this is normally accomplished by seam welding the sheets together to form a fluid tight hollow plate. Heretofore, ~~plate-coils~~ heat exchanger plates have been constructed to operate under internal pressure caused by pumping the heat exchange medium through the ~~coil~~ plate. To resist internal pressure and to prevent the sides of the ~~coils~~ plates from deforming, depressions or dimples are formed along the ~~plate-coil~~ plate. An example of similar ~~plate-coils~~ heat exchanger plates and their use are described in U.S. Patent 6,328,099 to Hilt et al. and U.S. Patent 6,460,614 to Hamert et al.

[004] During the normal operation of the heat exchanger the bulk material tends to accumulate within the dimples or spot welds and continues to collect to a point where the efficiency of the heat exchanger is greatly reduced and must be cleaned to remove the material residue from the dimples and surrounding exterior surface of the coil plates. In some circumstances, the material is allowed to collect to a point where the material will bridge between adjacent plate-coil plates; this not only reduces the heat transfer efficiency of the heat exchanger, but also restricts the flow of the material through the heat exchanger. These circumstances are very undesirable because the operation of heat exchanger must be shut down for a period of time to clean the coil plates, which many times means the material production line is also shut down, resulting in loss of production and ultimately loss in profits.

[005] Therefore, a need exists for a new and improved flat-plate-coil flat heat exchanger plate that can be used for bulk material heat exchangers which reduces the tendency for the material to accumulate on the coil plates. In this regard, the present invention substantially fulfills this need. In this respect, the flat-plate-coil flat heat exchanger plate according to the present invention substantially departs from the conventional concepts and designs of the prior art, and in doing so provides an apparatus primarily developed for the purpose of increasing the efficiency of bulk material heat exchangers and reducing down time thereof.

SUMMARY OF THE INVENTION

[006] In accordance with the present invention, a flat-plate heat exchanger-coil flat heat exchanger plate for use in bulk material heat exchangers is provided. The flat heat exchanger plate coil comprises a plurality of sheets secured together along the edges thereof to form a fluid tight and hollow plate coil that is generally rectangular in shape. The sides of the heat exchanger plate coil are substantially smooth and free of depressions, indentations, ridges or the like. The flat heat exchanger plate coil includes an internal fluid flow passage defined by a plurality of flow diverters, which are positioned within the hollow space of the plate coil. Heat exchange medium is directed into an inlet nozzle formed in the plate-coil plate and out of a similarly designed exit nozzle formed in the plate-coil plate. Unlike a conventional plate-coils heat exchanger plate, the coil plate of the present invention is designed to operate under a negative internal pressure opposed to a positive internal pressure. Because the plate-coil heat exchanger plate is designed to operate under a negative internal pressure the dimples or otherwise depressions formed on the exterior surfaces of prior art plate-coils heat exchanger plate to withstand internal positive pressure loading are eliminated. In doing so accumulation of material on the exterior surface of the plate-coil heat exchanger plate is reduced to a very minimal amount.

[007] To withstand the negative pressure within the plate-coils flat heat exchanger plate, pressure-resisting elements are positioned within the plate-coil heat exchanger plate and may be unattached or secured to either or both internal surfaces of the sidewalls of the coil-plate heat exchanger plate. The pressure resisting members or pressure resistor members prevent the sidewalls of the plate-coil heat exchanger plate

from deforming or collapsing inward due to the negative operating pressure present within the ~~plate-coil~~ heat exchanger plate.

[008] During initial filling of the ~~plate-coils~~ heat exchanger plate with a heat exchange medium or during non-operational periods of the ~~coils~~ plates, the sides of the ~~coil plate~~ may tend to bow outward causing the ~~coil plate~~ to inflate due to the low positive pressure exerted by the heat exchange medium present within the ~~coil plate~~ in a static state. To prevent this from occurring, pressure restraint members are positioned within the ~~coil plate~~ and are secured to both sides of the ~~coil plate~~, thereby preventing the interior distance between the sides of the ~~coils~~ plates from increasing.

[009] Flow diverters are positioned within the flow passage of the ~~plate-coil~~ flat heat exchanger plate and create flow channels for the heat exchange medium to follow. The flow diverters can be formed to any suitable shape from flat stock material or from solid or hollow sectional material and in some applications plastic mouldings could be employed. In addition, the flow diverters can also aid the pressure resistors in preventing the ~~plate-coil~~ flat heat exchanger plate from collapsing due to internal negative pressures.

[0010] An additional advantage of operating the ~~plate-coil~~ heat exchanger plate under negative pressure is the ability to use manifolds that are less expensive and less heavy duty than that of the manifolds required for ~~plate-coils~~ heat exchanger plates that operate under positive pressure. A lighter duty and less costly manifold, typically a section of pipe or any hollow section material can be used.

[0011] In additional embodiments of the ~~plate-coil~~ flat heat exchanger plate of the present invention, the ~~coils~~ plate is ~~are~~ constructed with tapered sides, which is beneficial in the flow of fine particulate material. The increasing width of the material flow path due to the tapered design of the ~~plate-coil~~ plate will reduce pressure build-up in the material, thereby making it less likely for particles to accumulate on the sides of the ~~plates~~ plate-coils.

[0017] Figure 1 is a side elevation view of an embodiment of ~~flat-plate-coil~~ flat heat exchanger plate of the present invention.

[0018] Figure 2 is an isometric view of the preferred embodiment of the bulk material heat exchanger constructed in accordance with the principles of the present invention in use with the ~~flat-plate-coils~~ flat heat exchanger plate of the present invention.

[0019] Figure 3a is a cross sectional view of an end of an embodiment of the ~~flat-plate-coil~~ flat heat exchanger plate of the present invention illustrating one possible method of adjoining the sheets of the ~~coil~~ plate.

[0020] Figure 3b is a cross sectional view of an end of an embodiment of the ~~flat-plate-coil~~ flat heat exchanger plate of the present invention illustrating a second possible method of adjoining the sheets of the ~~coil~~ plate.

[0021] Figure 3c is a cross sectional view of an end of an embodiment of the ~~flat plate-coil~~ flat heat exchanger plate of the present invention illustrating a third possible method of adjoining the sheets of the ~~coil~~ plate.

[0022] Figure 3d is a cross sectional view of an end of an embodiment of the ~~flat plate-coil~~ flat heat exchanger plate of the present invention illustrating a fourth possible method of adjoining the sheets of the ~~coil~~ plate.

[0023] Figure 3e is a cross sectional view of an end of an embodiment of the ~~flat plate-coil~~ flat heat exchanger plate of the present invention illustrating a fifth possible method of adjoining the sheets of the ~~coil~~ plate.

[0024] Figure 4 illustrates a pressure resistor and a possible attachment method thereof to the ~~flat plate-coil~~ flat heat exchanger plate of the present invention.

[0025] Figure 5a illustrates a pressure restraint member and a possible attachment method thereof to the ~~flat plate-coil~~ flat heat exchanger plate of the present invention.

[0026] Figure 5b illustrates a pressure restraint member and a possible alternate attachment method thereof to the ~~flat plate-coil~~ flat heat exchanger plate of the present invention.

[0027] Figure 5c illustrates an alternate pressure resistor attached to a single side of the ~~flat plate-coil~~ flat heat exchanger plate of the present invention.

[0028] Figure 5d illustrates the pressure resistor of Fig. 5c and a possible arrangement method thereof to the ~~flat plate-coil~~ flat heat exchanger plate of the present invention.

[0029] Figure 5e illustrates the pressure resistor of Fig. 5c used as a pressure restraint member and a possible attachment method thereof to the ~~flat plate-coil~~ flat heat exchanger plate of the present invention.

[0030] Figure 6a is a cross sectional view taken across a flow diverter of the ~~coil~~ plate in Figure 1.

[0031] Figure 6b is a cross sectional view taken across an alternate flow diverter of the ~~coil~~ plate in Figure 1.

[0032] Figure 6c is a cross sectional view taken across an alternate flow diverter of the ~~coil~~ plate in Figure 11, discussed below.

[0033] Figure 7 is a side elevation view of an alternate embodiment of the ~~flat plate-coil~~ flat heat exchanger plate of the present invention.

[0034] Figure 8a is a cross sectional view taken through a flow diverter of the ~~coil plate~~ in Figure 7.

[0035] Figure 8b illustrates an alternate embodiment of Figure 8a.

[0036] Figure 9 is a side elevation view of the tapered embodiment of the ~~flat plate-coil~~ flat heat exchanger plate of the present invention.

[0037] Figure 10a is a cross sectional view of the ~~coil plate~~ in Figure 9.

[0038] Figure 10b illustrates an alternate embodiment of Figure 10a.

[0039] Figure 11 is a side elevation view of an alternate embodiment of the ~~flat plate-coil~~ flat heat exchanger plate of the present invention.

[0040] Figure 12 is a front elevation view of the ~~flat plate-coil~~ flat heat exchanger plate of Figure 11.

[0041] Figure 13a is an isometric view of an alternate embodiment of a combined flow diverter and pressure resistor of the present invention.

[0042] Figure 13b is a front elevation view of an alternate embodiment of the ~~flat plate-coil~~ flat heat exchanger plate of the present invention.

[0043] Figure 13c is an isometric view of an alternate combined flow diverter and pressure resistor of the ~~coil plate~~ in Figure 13b.

[0044] Figure 14 is a front elevation view of an alternate embodiment of the ~~flat plate-coil~~ flat heat exchanger plate of the present invention.

[0045] Figure 15 is a cross sectional view of the ~~coil plate~~ in Figure 14.

[0046] Figure 16 illustrates the method of incorporating a removable seal between adjacent ~~flat plate-coils~~ flat heat exchanger plates.

[0047] Figure 17 is a side elevation view of an embodiment of the ~~flat plate-heat exchanger-coil~~ flat heat exchanger plate of the present invention illustrating the typical placement of support holes for supporting the plate-coil.

[0048] Figure 18 is a cross sectional view of one support hole of FIG. 17.

[0049] Figure 19 is a side elevation view of an embodiment of the ~~flat plate-heat exchanger-coil~~ flat heat exchanger plate of the present invention illustrating a typical placement of location lugs, indents, support lugs and lifting lug for the plate-coil.

[0050] Figures 20a and 20b illustrate a method of automated cleaning of the ~~flat plate-coils~~ flat heat exchanger plates of the present invention.

[0051] Figures 21a, 21b and 21c illustrate an alternate method of automated cleaning of the ~~flat plate-coils~~ flat heat exchanger plates of the present invention.

[0052] Figure 22a illustrates an additional alternate method of automated cleaning of the ~~flat plate-coils~~ flat heat exchanger plates of the present invention, where a plurality of cam elements are positioned along the length of a support bar.

[0053] Figure 22b illustrates one possible cam arrangement for use in the method of automated cleaning of the ~~flat plate-coils~~ flat heat exchanger plates illustrated in Figure 22a.

[0054] Figure 22c illustrates a second one possible cam arrangement for use in the method of automated cleaning of the ~~flat plate-coils~~ flat heat exchanger plates illustrated in Figure 22a.

[0055] Figure 23 illustrates an example of a cam arrangement to provide horizontal, back and forth movement of the ~~plate-coils~~ flat heat exchanger plates.

[0056] Figure 24 illustrates an example of a cam arrangement to provide horizontal side-to-side movement of the ~~plate-coils~~ flat heat exchanger plates.

[0059] In Figures 1 and 2 a new and improved ~~flat plate-heat exchanger-coil~~ flat heat exchanger plate 10 of the present invention for the purpose of increasing the efficiency of bulk material heat exchangers and reducing down time thereof is illustrated and will be described. More particularly, in FIG.1, the ~~flat plate-heat exchanger-coil~~ flat heat exchanger plate 10 has a flat, generally rectangular metal body 12 having two opposing side sheets 14, two opposing longitudinal edges 16, and two opposing transverse edges 18. The two side sheets 14 are sealed to each other along the borders of the two longitudinal and two transverse edges 16 and 18 defining an open interior space. Figures 3a – 3d illustrate possible methods of seaming the edges of the ~~flat plate-heat exchanger-coil~~ flat heat exchanger plate 10. Heat exchange medium inlet and exit nozzles 20 and 22 are provided in fluid communication with the open interior space and can be arranged for example along a common longitudinal edge 16.

[0060] Each side sheet 14 is substantially smooth and free of depressions and/or dimples or the like. The phrase “substantially smooth” is to be defined in the context of this application for U.S. Letters Patent as free from ridges, depressions, and dimples or the like created in the sides of the ~~flat plate-heat exchanger-coil~~ flat heat exchanger plate during the manufacture thereof.

[0061] Prior art ~~plate-coils~~ heat exchanger plates are manufactured with dimples and/or depressions formed on the sides thereof and welded together to increase the resistance of the sides from bowing outward due to a positive internal operating pressure

created by pumping a heat exchange medium through the ~~coil plate~~. These dimples are a drawback to prior art ~~plate-coils plates~~ because in service bulk material tends to accumulate in these dimples which has a negative two fold effect. First, the heat transfer between the bulk material and the ~~coil plate~~ is reduced by a loss of effective surface area of the ~~coil plate~~ and second the bulk material may be allowed to accumulate to a point where the material bridges between adjacent ~~coils plates~~ thereby impeding the flow of the material through the heat exchanger. Once this occurs, the heat exchanger must be removed from service and cleaned, which results in undesirable down time of the material production line. To overcome the drawbacks of the prior art, the ~~flat-plate heat exchanger-coil flat heat exchanger plate~~ 10 of the present invention is designed to operate under a negative internal pressure, thereby eliminating the need to create dimples on the sides of the ~~coil plate~~.

[0062] Turning to Figure 2, numerous ~~flat-plate-coils flat heat exchanger plates~~ 10 are illustrated in an exemplary in-use arrangement positioned within a typical bulk material heat exchanger 24. The ~~flat-plate heat exchanger-coils flat heat exchanger plates~~ 10 are arranged side-by-side in a spaced relationship within the shell of the bulk material heat exchanger 24. The inlet nozzle 20 of each ~~coil plate~~ 10 is connected to a common heat exchange medium supply manifold 26 and the exit nozzle 22 of each ~~coil plate~~ is also connected to a common heat exchange medium return manifold 28. The inlet nozzle 20 and the exit nozzle 21 can be formed to any suitable shape, such as but not limited to a rectangle or a circle. In operation, a vacuum source is provided at the heat exchange return manifold 28 and the flow of the heat exchange medium is indicated by arrows 30, where the heat exchange medium enters the supply manifold 26 and is distributed to each of the inlet nozzle 26 of each ~~coil plate~~ 10. The heat exchange medium is then drawn up and through each ~~coil plate~~ 10 and ultimately out of the heat exchange medium return manifold 28. Arrows 32 indicate the flow of the bulk material, and the material flows through the heat exchanger and across the ~~coils plates~~ 10, typically under the force of gravity. With this arrangement, the bulk material heat exchanger 24 operates as a counter flow type heat exchanger.

[0063] The ~~coil flat heat exchanger plate~~ 10 as indicated above, is designed to operate under a negative internal pressure or vacuum as low as about 10 psi (70kPa) on a vacuum gage. To prevent the side sheets 14 of the ~~flat-plate heat exchanger-coil flat heat exchanger plate~~ 10 from collapsing at least one pressure resistor member 34 is positioned and strategically arranged within the interior space of the ~~coil plate~~. During non-operational periods of the ~~coil plate~~ 10, a positive internal pressure may be present due to the hydrostatic pressure of the heat exchange medium present within the ~~coil plate~~ in a static state. To prevent inflation or deforming of the sides of the ~~coil plate~~ 10, at least one pressure restraint member 36 can be included and is positioned and strategically arranged within the interior space of the ~~coil plate~~.

[0064] At least one flow diverter 38 is positioned within the ~~coil flat heat exchanger plate~~ 10 to create flow passage for the circulating heat exchange medium to flow through. Preferably, flow diverters 38 are arranged to create a serpentine-like flow

path for the heat exchange medium. The flow diverters 38 can also aid the pressure resistor members 34 in preventing the sides of the ~~coil~~ plate 10 from collapsing.

[0065] Figure 4 illustrates a pressure resistor member 34 positioned between the interior surfaces 40 of the side sheets 14 of the ~~coil~~ flat heat exchanger plate 10. The pressure resistor member 34 is generally cylindrical and is attached at one end to one interior surface 40 of a single side sheet 14. Preferably, the pressure resistor member 34 is attached at one end to the interior surface 40 by a weld 42 with the opposite end of the pressure resistor member free from attachment to the opposing interior surface of the other side sheet. In a preferred embodiment, the pressure resistor member 34 is of a length equal to the distance between the interior surfaces 40 of the ~~coil~~ plate side sheets 14. In the manufacture of the ~~coil~~ plate 10, a predetermined number and arrangement of pressure resistors 34 are first attached in a desired pattern to the interior surface 40 of the side sheets 14 before the side sheets are assembled with the ~~coil~~ plate 10.

[0069] Turning now to Figure 6a, which is a cross sectional view of the ~~flat plate heat exchanger-coil~~ flat heat exchanger plate 10 as illustrated in Figure 1. This figure shows an example of one possible form of a flow diverter 38 positioned within the plate ~~coil~~ 10 and between the side sheets 14. In this example, the flow diverter 38 is a strip of material having a bend of approximately 90 degrees along a centerline thereof. The flow diverter 38 includes a plurality of holes 64 formed therethrough along the centerline thereof. The holes 64 allow the flow diverter 38 to be positioned about an arrangement of pressure resistors 34 and/or pressure restraint members 36. Referring back to Figure 1, which illustrates the placement of multiple flow diverters 38 about the pressure resistors 34 and pressure restraint members 36 to create a serpentine flow path for the heat exchange medium. The positioning of the flow diverters 38 as illustrated is for exemplary purposes only as the flow diverters can be arranged in any manner to create a desired flow path for the heat exchange medium.

[0070] Figure 6b illustrates an example of a combined flow diverter and pressure resistor 38 positioned within the flat heat exchanger plate ~~coil~~ 10 between the side sheets 14. In this example, the combined flow diverter and pressure restraint 38 is a strip of material having opposed edges bent orthogonal to the side sheets 14 to form two legs 15. These legs act as pressure resistors to prevent the collapse of the plate ~~coil~~ 10 when operated under a negative pressure. The diagonal web 17 includes a plurality of locating holes 64, and creates to flow passages 19 for the heat exchange medium.

[0071] Figure 6c illustrates an additional example of a combined flow diverter and pressure resistor 38 in the form of a corrugated formed sheet of material positioned within the flat heat exchanger plate ~~coil~~ 10 and secured to the interior surfaces 40 of the side sheets 14.

[0072] Turning to Figures 7, 8a and 8b an alternate embodiment of the ~~flat plate heat exchanger-coil~~ flat heat exchanger plate 10 and flow diverters 38 of the present invention is illustrated and now will be described. In this embodiment, the flow diverters 38 are formed from a solid rod or tube, which are bent and positioned within the ~~coil~~

plate 10 to create a desired heat exchange medium flow path. The pressure resistors 34 and the pressure restraint members 36 are strategically positioned and attached to the side sheets 14 of the ~~coil~~ plate 10 to aid in the correct placement of the formed flow diverters 38. Preferably, the pressure resistors 34 and restraints 36 are positioned to alternate from side to side of the flow diverters 38, as illustrated in Figure 7. Figure 8a is an enlarged partial cross section of the ~~coil~~ plate 10 illustrated in Figure 7 and this figure shows a flow diverter formed from a solid rod and illustrates the method of positioning the pressure resistors 34 and/or restraints 36 on opposite sides of the flow diverter 38 to aid in the positioning and retention thereof. Figure 8b illustrates an alternate embodiment of the flow diverter 38 illustrated in Figure 8a. In this embodiment, the flow diverter is a tube. The flow diverters 38 illustrated in Figures 7, 8a and 8b are of a material having a circular cross section for exemplary purposes only and should not limit the possibility of using material of other cross sectional shapes.

[0073] Referring now to Figures 9, 10a and 10b, which illustrate an additional embodiment of the ~~flat plate heat exchanger coil~~ flat heat exchanger plate 10 of the present invention. In this embodiment the thickness of the ~~coil~~ plate 10 decreases in the direction from one transverse edge to the second transverse edge. Preferably, the thickness of the ~~coil~~ plate 10 decreases in the direction of the flow of bulk material across the coil. Preferably in this particular embodiment incremental steps 66 decrease the thickness of the ~~coil~~ plate 10. Most preferably, the steps 66 and thickness of the ~~coil~~ plate 10 correspond with the various diameters of rod or tube used for the flow diverters 38. Figure 9 also illustrates an additional possible arrangement of the flow diverters 38 to create a serpentine flow path for the heat exchange medium. As in all of the aforementioned embodiments of the ~~flat plate coil~~ flat heat exchanger plate 10, the flow diverters in this embodiment can aid the pressure resistors 34 in preventing the side sheets 14 of the ~~coil~~ plate 10 from collapsing. During the manufacture of this embodiment of the ~~flat plate coil~~ flat heat exchanger plate 10 the longitudinal edges 16 are cut to match the step profile of the side sheets 14 of the ~~coil~~ plate. Preferably, the longitudinal edges 16 are laser cut to match the step profile of the side sheets 14.

[0074] Figure 10a is a side elevation view illustrating an example of one method of creating a tapered ~~flat plate coil~~ flat heat exchanger plate 10. In this example, the side sheets 14 of the ~~plate~~ plate 10 are formed by overlapping sections of sheet metal 68, as illustrated, which are then welded together. The thicknesses of the flow diverters 38 are equal to the distance between the interior surfaces 40 of the side sheets 14 for each step 66 of the ~~coil~~ plate 10. For exemplary purposes only, the flow diverters in this figure are illustrated as solid rods.

[0075] Figure 10b illustrates a side elevation view illustrating an example of a second method of creating a tapered ~~flat plate coil~~ flat heat exchanger plate 10. In this example, a single sheet is used for each side sheet 14 and the sheet is bent inward at various positions along the length thereof to create the required stepped profile of the side sheet. The thickness of the flow diverters 38 are equal to the distance between the interior surfaces 40 of the side sheets 14 for each step 66 of the ~~coil~~ plate 10. For exemplary purposes only, the flow diverters in this figure are illustrated as tubes.

[0076] Referring now to Figures 11, 12 and 13, which illustrate a third embodiment of the ~~flat plate heat exchanger coil~~ flat heat exchanger plate 10 of the present invention and an additional example of a flow diverter assembly 38 for use with a tapered or parallel plate ~~coil~~. The flow diverter assembly 38 of this embodiment includes a plurality of tapered flow diverter strips 70 which are interlocked with a plurality of flow control strips 72. Preferably, the flow control strips 72 and the tapered flow diverter strips 70 are interlocked orthogonal to each other. The flow control strips 72 include a plurality of reduced sections 74, which are formed to be positioned between adjacent tapered flow diverter strips 70 and serve to control the amount of heat exchange medium that passes each flow control strip. The flow diverter 38 of this embodiment is also used to prevent the tapered ~~coil~~ plate 10 from collapsing under negative operating pressure. Pressure restraint members 36 (not illustrated) may also be used in the same manner as described previously to prevent inflation of the ~~coil~~ plate 10 and to help position the flow diverter 38 within the ~~coil~~ plate.

[0077] Referring to Figures 13b and 13c, which illustrate a fourth embodiment of the ~~flat plate coil~~ flat heat exchanger plate 10 of the present invention and an additional example of a plurality of flow diverters 38 for use with tapered or parallel ~~flat plate coils~~ flat heat exchanger plate. The flow diverter 38 of this example is a tapered or parallel strip of material formed in a serpentine shape and includes a heat exchange medium flow control leg 39. The flow control leg 39 restricts the flow of heat exchange medium into each chamber 41 to ensure an even flow rate of heat exchange medium within each chamber across the plate ~~coil~~. The flow diverter 38 of this example is also used to prevent the plate ~~coil~~ 10 from collapsing under negative operating pressure. In addition to the flow diverters 38, pressure restraint members 36, not illustrated, can be used in the same manner as previously described to prevent inflation of the plate ~~coil~~ 10 and to aid in the positioning of the flow diverters 38 within the plate ~~coil~~.

[0078] Turning to Figures 14 and 15 a fifth method of creating a tapered ~~flat plate coil~~ flat heat exchanger plate 10 is illustrated. The flat side sheets 14 are in parallel planes and increase in width in a direction from one transverse edge 18 of the ~~coil~~ plate 10 to second transverse edge 18 of the ~~coil~~ plate. Preferably, the thickness of the ~~coil~~ plate 10 remains constant along the length of the ~~coil~~ plate. The gradual increase in width of the ~~coil~~ plate 10 creates a greater volume between adjacent ~~coils~~ plates in a bulk material heat exchanger, which releases pressure build-up in particulate material flowing through the heat exchanger. The flow diverters 38 of this example are of an open channel material having a closed side 76 and an open side 78 that includes a pair of flanges 80. The plate ~~coil~~ 10 is constructed by first attaching a plurality of flow diverters 38 to the interior surface 40 of one side sheet 14 by welds 82. The plurality of flow diverters 38 are attached to the side sheet 14 in a desired pattern to create a flow path for the heat exchange medium. Then the second side sheet 14 is attached to the ~~coil~~ plate 10 and the flow diverters 38 by welds 84 from the exterior side of the second sidewall. Preferably, the welds are laser welded. This method of construction provides for the placement of the flow diverters 38 within the ~~coil~~ plate and allows the flow diverters to function as pressure resistors and restraints.

[0079] Now turning to Figure 16, a removable seal 86 may be positioned between adjacent ~~plate-coils~~ flat heat exchanger plates 10 to retain the flow of material 88 therebetween. The seal may be removed to help facilitate the cleaning of the ~~coils~~ plates 10 or by adjusting the vertical angle of the seal to control the flow of material 88 between the ~~coils~~ plates.

[0080] Referring to Figures 17 and 18, which illustrate a typical placement of support holes 90 through the ~~flat-plate-coil~~ flat heat exchanger plate 10. The support holes 90, which may be of any desired shape, are formed through both side sheets 14. A tubular sleeve 91 is placed in the support holes 90 then welded to both side sheets 14 and then dressed flushed with the exterior surfaces of the side sheets. The support holes 90 are typically used in supporting the ~~flat-plate-coil~~ flat heat exchanger plate 10 within a heat exchanger.

[0081] Now turning to Figure 19, which illustrates the capability of incorporating the placement of location lugs 92, which extend from the ends of the ~~coil~~ flat heat exchanger plate 10, indents 94 formed into the ends of the ~~coil~~ plate, support lugs 96 extending from the edges of the body of the ~~coil~~ plate and a lifting lug 98 extending from the top of the ~~coil~~ plate. Currently, plate heat exchangers are manufactured with supports below the ~~plate-coils~~ plates which can impede the flow of bulk material and also increase the overall height of the heat. The incorporation of location lugs 92, indents 94, support lugs 96, or a lifting lugs 98 eliminates the need for the supports below the ~~plate~~ plates and improves the flow path for the bulk material. The overall height of the heat exchanger can be reduced correspondingly.

[0082] Referring to Figures 20a and 20b, an additional embodiment the ~~flat-plate-coil~~ flat heat exchanger plate 10 is illustrated and will be described. In this embodiment, the ~~flat heat exchanger plate~~ 10 are is designed and manufactured such that upon removal of the negative operating pressure the flat heat exchanger plate ~~coil~~ sides 14 will slightly inflate due to a positive internal pressure created exerted by the heat exchange medium. Isolating the vacuum source and allowing the heat exchange medium to develop a desired hydrostatic pressure within the ~~plate-coils~~ flat heat exchanger plates 10 can achieve the slight inflating of the plate ~~coil~~ sides 14. Upon reestablishing the negative operating pressure, the plate ~~coil~~ sides 14 return to a non-inflated position. Preferably, the hydrostatic pressure is allowed to reach a about 5 PSI (34 kPa) and is only applied for a short duration. The duration is at least 1 second. Preferably the duration is from about 1 to about 10 seconds and most preferably, the duration is about 5 seconds. An automated pulsing system 100 can be incorporated in the heat exchange medium system 102 to cause the inflation-deflation cycle of the ~~flat-plate-coils~~ flat heat exchanger plates 10 at a predetermined frequency.

[0083] Incorporating the above cyclic inflation of the ~~flat-plate-coils~~ flat heat exchanger plates 10 in, for example a bulk material heat exchanger would be beneficial in processing fine particulate materials which tend to bridge across narrow spaces such as the gaps between adjacent ~~flat-plate-coils~~ flat heat exchanger plates, which creates

blockages in the flow of the material. By inflating the ~~plate-coil~~ flat heat exchanger plate sides 14 by a small fraction of an inch the gap between adjacent ~~plate-coils~~ flat heat exchanger plates decreases thus compressing any bulk material in the gap. On returning the ~~plate-coil~~ flat heat exchanger plate sides 14 to the non-inflated position, the gap between adjacent plate coils increases to the normal operation gap and the compressed bulk material is dislodged from the sides. This system provides for the automated, self-cleaning of ~~flat-plate-coils~~ flat heat exchanger plates 10, which reduces operating costs and service time of the ~~flat-plate-coils~~ flat heat exchanger plates.

[0084] In an additional embodiment of the ~~flat-plate-coils~~ flat heat exchanger plate a system of providing automated, self-cleaning ~~flat-plate-coils~~ flat heat exchanger plates 10 is illustrated in Figures 21a, 21b and 21c. In this embodiment, the self-cleaning system includes a lift means 106 for lifting the ~~plate-coils~~ flat heat exchanger plates 10 to aid in the removal of any bulk material that has accumulated on the exterior surfaces of the ~~plate-coils~~ flat heat exchanger plates. In one example, the ~~flat-plate-coils~~ flat heat exchanger plates 10 are supported on a bar 104 passing through sleeves 91, which can be extended as illustrated to maintain the flat heat exchanger plate coil spacing. Referring back to Figure 2, a flexible connection is incorporated between the flat heat exchanger plate-coil inlet nozzles 20 and the inlet manifold 26, and a similar flexible connection is incorporated between the flat heat exchanger plate coil exit nozzles 22 and the outlet manifold 28. In Figures 21a and 21b, the ends of the bar 104 are supported by the casing of the bulk material heat exchanger 24. The lift means 106 for lifting and rapidly dropping the bar 104 and the ~~flat-plate-coils~~ flat heat exchanger plates 10 is attached to the bar. The lift means 106 would raise the bar 104 off of its supports 105 by a fraction of an inch, as illustrated in Figure 21a and then allowed to fall under the effect of gravity back onto the supports as illustrated in Figure 21b. By the lift means 106, the ~~flat-plate-coils~~ flat heat exchanger plates 10 supported by the bar 104 are raised and dropped resulting in developing a shock wave through the ~~flat-plate-coil~~ flat heat exchanger plates. The resultant shock wave will dislodge any present bulk material blockage between adjacent ~~coils~~ flat heat exchanger plates 10.

[0085] The lift means 106 could incorporate, for example a cam 108 that is driven by motor 110. The cam 108 is in contact with the cam follower 112 attached to the end 114 of the bar 104. The cam 108 can include a gradual lift profile about a predetermined number of degrees of rotation and a flat profile about a predetermined number of degrees of rotating. Figure 21c illustrates an example of a cam profile that could be used. The lift profile of the cam 108 will gently raise the support bar 104 and the ~~plate-coils~~ flat heat exchanger plates 10 to a maximum predetermined lift that is a fraction of an inch. The flat profile 109 of the cam 108 will cause the bar 104 to free fall under the force of gravity the distance it was originally raised causing the bar to impact its support 105, thereby forming a shock wave through the ~~plate-coils~~ flat heat exchanger plates 10.

[0086] Referring to Figures 22a, 22b and 22c, an additional example of the lift means 106 is illustrated and will be described. A cam 116 for each flat heat exchanger plate coil 10 can be incorporated into the support bar 104 and a cam follower 118 can be incorporated into each sleeve 91. Upon rotation of the support bar 104, for example by

attaching an end 114 of the support bar to the shaft of a motor, the ~~plate-coils~~ flat heat exchanger plates 10 are raised and lowered based upon the profile of each cam 116. Preferably, the maximum lift of each cam 116 is sequentially offset so that each flat heat exchanger plate ~~coil~~ 10 will be raised and lowered in predetermined sequence thus creating a shearing effect in the material between each adjacent flat heat exchanger plate ~~coil~~. Turning to Figure 22b, the cam profile of the cam 116 can include a steep profile section 120 which would cause the flat heat exchanger plate ~~coil~~ 10 to fall under the force of gravity a predetermined distance in accordance with the profile section 120. This fall would send a shock wave through the flat heat exchanger plate ~~coil~~ 10 and aid in the removal of the material from of the exterior surface thereof.

[0087] Figure 22c illustrates an additional example of a cam profile for the cam 116 that could be used. In this example, the ~~plate-coils~~flat heat exchanger plates would be raised and lowered in a predetermined sequence thus creating a shearing effect the material between each adjacent flat heat exchanger plate ~~coil~~. The incorporation of a scraper element 122 into the bearing surface of the sleeve 91 would act to keep the surface of the cam 116 clear of material debris that could impede the operation of the cam.

[0088] Referring to Figure 23, which illustrates an example of a cam arrangement including an eccentric cam 116 and cam followers 118 incorporated into the sleeve 91 of a flat heat exchanger plate ~~coil~~. In this example, upon rotation of the support bar 104 the cam followers 118 would follow the profile of the cam 116 and flat heat exchanger plate ~~coil~~ would translate horizontally back and forth. Such as described above a plurality of cams 116 would be incorporated along the length the support bar 104 with the maximum lift of each cam 116 offset from each other to create a shearing effect in material between each adjacent plate ~~coil~~.

[0089] Referring to Figure 24, which illustrates an additional cam arrangement example including a plurality of lateral cams 116 cut into the support bar 104 and a cam follower 118 incorporated into the sleeve 91 of each plate ~~coil~~ 10. In this example, upon rotation of the support bar 104 the cam follower 118 would follow the profile of the lateral cam 116 cut into the support bar 104 and the ~~plate-coils~~plates 10 would translate horizontally from side-to-side in unison. In addition, the sleeves are extended to provide spacing for adjacent ~~plate-coils~~plates 10. The side-to-side, unison movement of the ~~plate coils~~plates 10 aids in dislodging bulk material accumulated between adjacent ~~plate coils~~plates.

[0090] A method of automated cleaning of the exterior surfaces of adjacent flat heat exchanger plates 10 ~~plate-coils~~ is provided and includes the steps of providing at least two flat heat exchanger plates ~~plate-coils~~ 10 arranged side-by-side in a spaced relationship, wherein the flat heat exchanger plates ~~plate-coils~~ include a heat exchange medium inlet nozzle and an exit nozzle 20 and 22. Attaching the heat exchange medium inlet 20 and exit nozzles 22 to a heat exchange medium supply system 102, wherein the supply system includes a vacuum source which is attached to the heat exchange medium exit nozzles for creating a negative operating pressure within the flat heat exchanger

~~plates plate coils~~. Isolating the vacuum source allowing the heat exchange medium to develop a predetermined desired hydrostatic pressure within the flat heat exchanger plates plate coils 10 to slightly inflate the flat heat exchanger plates plate coils to reduce the space between the flat heat exchanger plates plate coils and compress any bulk material that is accumulated on the exterior surfaces of the sides of the flat heat exchanger plates plate coils. And reconnecting the vacuum source to reestablish the negative operating pressure and thus deflating the flat heat exchanger plates plate coils 10 to increase the space between the coils-plates and dislodge the compressed bulk material.

[0091] This method may also include connecting a pulsing 100 system between the vacuum source and the exit nozzles of the flat heat exchanger plates 10 ~~plate coils~~ to isolate the vacuum source and reconnect the vacuum source in a cyclic manner having a predetermined frequency.

[0092] ~~—————~~ An additional method of automated cleaning of the exterior surfaces of adjacent plate coils is provided and includes the steps providing at least two plate coils 10 arranged side-by-side in a spaced relationship, wherein the plate coils are supported by a support bar 104 having the ends 107 thereof supported by supports 105. Attaching a lift means 106 for lifting the support bar 104 off of the supports 105 to the ends 107 of the support bar. Raising the support bar 104 and supported coils 10 by the lift means 106 a predetermined distance off of the supports 105. Dropping the support bar 104 under the force of gravity the predetermined raised distance onto the supports 105 to send a shock wave through the coils 10 to dislodge bulk material that has accumulated on the exterior surfaces of the coils.

[0093] ~~—————~~ An additional method of automated cleaning of the exterior surfaces of adjacent plate coils comprising is provided and includes the steps of providing at least two plate coils 10 arranged side-by-side in a spaced relationship, wherein each plate coil is supported on a cam 116 attached to a support bar 104 and wherein a support sleeve 91 of the plate coil includes a cam follower 118 which is in contact with the profile of the cam. And rotating the support bar 104 so that the cam follower 118 of sleeve 91 of each plate coil 10 follows the profile of the cam 116 which it is engaged so that the plate coil is raised and lowered in accordance with the profile of the cam so as to remove material that has accumulated on the exterior surfaces of the plate coil

[0094] ~~—————~~ Preferably in this method, the maximum lift of each cam 116 is offset by a predetermined number of degrees so that each plate coil 10 is raised and lowered in a predetermined sequential pattern so as to create a shearing effect of the material between the adjacent plate coils. Most preferably, the profile of the cam 116 includes a steep section 120 so that the plate coil 10 is caused to fall under the force of gravity a predetermined distance in accordance with the steep section of the cam profile so that a shock wave is sent through the plate coil to aid in the removal of the material. In addition, the sleeve 91 of the plate coil 10 may include a scraper element 122 that would act to keep the surface of the cam 116 clear of material debris that could impede the operation of the cam.

[0095] While a preferred embodiment of the ~~flat plate coil~~ flat heat exchanger plate 10 has been described in detail, it should be apparent that modifications and variations thereto are possible, all of which fall within the true spirit and scope of the invention. With respect to the above description then, it is to be realized that the optimum dimensional relationships for the parts of the invention, to include variations in size, materials, shape, form, function and manner of operation, assembly and use, are deemed readily apparent and obvious to one skilled in the art, and all equivalent relationships to those illustrated in the drawings and described in the specification are intended to be encompassed by the present invention.

ABSTRACT OF THE DISCLOSURE

A ~~flat plat plate heat exchanger coil~~ flat heat exchanger plate typically used in a bulk material heat exchanger is provided. The ~~flat plate heat exchanger coil~~ flat heat exchanger plate is designed to operate under a negative internal pressure to eliminate depressions or dimples that are typically formed into the sides of these types of heat exchanger coils during the manufacture process. With the removal of the depressions or dimples the tendency for bulk material to accumulate to the exterior surface of the ~~coil~~ plate is reduced, thereby increasing the service period of the ~~coil~~ plate. ~~The flat plate is also provided with methods of automated cleaning of the plate coil, such as applying a low positive internal pressure in a cyclic manner to dislodge material accumulated on the coil, bumping the coil to causing a shock wave through the coil or providing means to create a shearing effect between adjacent coils to dislodge material accumulated on the exterior of the coil.~~